




SAFETRED DIMENSION



TECHNICAL DATASHEET – UPDATE (12/2007)

VINYL

 0338-CPD-1002	EN 14041:2004 	Manufactured by: Tarkett-Marley Floors Ltd Lenham, Maidstone Kent ME17 20X UNITED KINGDOM
		EN 13845 Safetred Dimension

TECHNICAL DATA	STANDARDS	PROPERTIES
Classification	EN 685 Commercial Industrial EN 13845	Classes: 34 43 ES _r
Total thickness	EN 428	2.0mm
Total weight	EN 430	3 000 g/m ²
Safety Clean PUR reinforcement		Yes
Abrasion	EN 13845	< 10% particle loss
Residual indentation	EN 433	< 0.10mm
Furniture Leg	EN 424	No damage
Castor Chair	EN 425	No damage
Dimensional stability	EN 434	≤ 0.10%
Curl resistant to heat	EN 434	≤ 3mm
Reaction to fire	EN 13501-1 EN ISO 9239-1: IMO A653	B _f s1 with acrylic adhesive on wood > 8 kW/m ² Pass
Slip resistance	TRRL Pendulum 4S (wet) Surface Roughness DIN 51130	> 36 > 20µm R10
Electrostatic properties	EN 1815 EN 1081	< 2kV on concrete > 10 ¹⁰ ohms
Impact sound reduction	EN ISO 140-8 EN ISO 717/2 ΔL _w	ΔL _w = 6dB
Acoustic improvement	NF S 31-074	L _{n,e,w} = 75dB
Light fastness	EN ISO 105-B02	7
Chemical resistance	EN 423	Good resistance to everyday substances
Anti Fungal Treatment		Incorporates a biostat to resist fungal and bacterial growth
Thermal resistance Underfloor heating	EN 12524 DIN 52612	0.01 m ² K/W Suitable provided that the surface of the subfloor does not exceed 27°C
Colours		16
Form of delivery	EN 426	Rolls: 20 lm x 2 m

The above information is subject to modification for the benefit of further improvement.
 For more detailed information, please contact Tarkett.
 Follow Tarkett's installation and maintenance instructions carefully, these are available on request.