

Omnisports TRAINING



KEY POINTS

Description :

Vinyl sports floor covering over fibreglass mat with PVC foam backing. Sanitized® (anti-bacterial coating). Protected with Top Clean XP® (dirty-resistant treatment for ease of maintenance)

Type of installation :

- Glued Installation

Surface Texture :

Sorrent

Compatible Installation :

Association possible with a sub construction (Lumaflex type)

Installation instructions and maintenance guide :

On request

Dimensions (EN 426/EN 427) :



2 m



20.5 lm or 23 lm

Total thickness (EN 428/EN 429) :



5.0 mm (± 0,15mm)

Total weight (EN 430) :



4.23kg/sqm (± 500g)

EN 14041 : 2004



-collé sur support béton

-collé sur panneau de bois

Fabriqué à Tarkett Sedan SAS
2 avenue François Sommer
08200 SEDAN

OMNISPORTS TRAINING

EN 651

Classification according to EN 685



FIBA
STUDY CENTRE
Partner

TARKETT
BALANCED
CHOICE

42,6 %

Natural

100 %
21 %

Recyclable
Recycled content



| Properties | Standard | Omnisports TRAINING |
|--|-------------|---------------------|
| Vinyl Indoor sports flooring with elastic point area deformation | | |
| must be installed on a sub-construction to reach the requirements of the EN 14 904 standard | | |
| Sports properties | | |
| Friction | EN 13036-4 | 100 |
| Shock Absorption % | EN 14 808 | 19 |
| Vertical deformation | EN 14 809 | 1.0mm |
| Vertical ball rebound | EN 12235 | 98.4% |
| Specular Gloss | EN ISO 2813 | 11 |

| Classification | | |
|-------------------|------------|--|
| Reaction to fire | EN 13501-1 | Bfl-S1 en pose collée Cfl-S1 sur support Lumaflex |
| Formaldehyde | EN 717-1 | Absence de formaldehyde |
| | EN 717-2 | |
| Pentachlorophenol | EN 12673 | Absence de pentachlorophenol |

| Technical characteristics | | |
|--------------------------------|---------------|----------------------------|
| Wear Layer | EN 429 | 0.70 mm |
| Abrasion | EN ISO 5470-1 | 0.13 g |
| Resistance to indentation | EN 1516 | 0.16mm |
| Behaviour under a rolling load | EN 1569 | 0.22mm |
| Resistance to impacts | EN 1517 | Some marks, No degradation |

| Specific characteristics | | |
|---|---|--------------|
| Surface treatment | Anti bacteria and anti fungus treatment + Anti bacteria and anti fungus treatment | |
| Maintenance | | |
| Available 10 plain colours 4 wooden patterns | Yellow | Orange |
| | Forest Green | Royal Blue |
| | Sky Blue | Black |
| | Maple | Beech |
| | Red | Grey |
| | Field Green | Teal |
| | Oak Classic | Oak Gunstock |
| Compatible slabs: Concrete, asphalt screed, anhydrite screed or Lumaflex sub construction. Any deviation of the slab must be corrected prior installation (6mm under a 3m straight edge). We reserve the right to modify these specifications without, however, affecting their compliance with standards. | | |

Tarkett France – 2, rue de l'Égalité – 92748 Nanterre cedex – TÉL. +33(0)1 41 20 40 40 – FAX +33(0)1 41 20 47 05 – info@tarkett.com

S.A.S au capital de 30800000 euros – RCS Nanterre 410 081640

www.tarkett-sports.com



THE ULTIMATE
SURFACE EXPERIENCE

V1 30/04/2011