

B&K Carpet Protection Film - Tacbac FR

Base Material & Features:

Tacbac FR is manufactured from flame retardant polyethylene film with an anti-slip surface and coated on one side with an acrylic solvent based adhesive. The product is self wound (i.e. does not use release paper), and is manufactured in 90 micron thickness as standard. Tacbac FR is a lightweight and extremely strong / puncture resistant temporary protection film for carpets - self adhesive / peel clean after use.

Flame Retardant Accreditation:

- Tested and approved to LPS1207 LPCB Certificated cert. no. 1030a/01 Assessed ISO9001
- ISO459 - 2 : 1996 (oxygen index>23%) pass
- BS476 part 12 heat source C pass

Toxicity accreditation:

- Pr EN 2825 (smoke emission) <150 pass
- Pr EN 2826 (toxic gas emission) pass (analytical report available on request)

Product Details:

Product code: TACBAC T100FR: 0.60m x 100m roll (60m²)

Product code: TACBAC T101FR: 1.00m x 100m roll (100m²)

Product code: TACBAC T102FR: 1.20m x 100m roll (120m²)

Applications:

For use on carpet floor coverings (not for smooth surfaces). Apply to clean and dry carpets, free from dust and excessive loose fibres. Avoid stretching the film when applying. Reverse wound - adhesive side out to assist installation. Press Tacbac firmly onto carpet. Allow time for vapours to evaporate before applying Tacbac FR (this refers to vapours from newly glued down carpets and underlay). Tacbac FR can be used to protect carpets for up to 12 weeks - for longer - remove and renew. Correct application ensures a peel clean removal with no adhesive residue.

Advantages:

- Proven protective properties on major projects
- Effective protection for all carpeted surfaces
- Adheres to carpet without leaving residue
- Lightweight, reverse wound rolls
- Flame retardant - approved and certificated to LPS1207 standard LPCB
- Produced by ISO 9001 manufacturer

